


# Hålogaland Suspension Bridge, Narvik, Norway

IABSE Denmark Mini-seminar 2013

Lars Jensen COWI A/S





# Introduction

## Scope of Work:

- Basic design for 2 suspension bridge solutions incl. construction cost estimates
- Detailed design for 1 suspension bridge solution

## COWI Team:

- COWI Project management, global and aerodynamic analyses, cable structures, steel box girder, cable anchorages, approach viaducts
- Dissing+Weitling Architect
- Johs Holt Pylons incl. foundations
- NGI Expert rock cable anchorages and foundations

**Client: Norwegian Public Roads Administration, Region North**







## Hålogaland Bridge

- 2007-2008: Basic Design and construction cost estimates
- 2009-2010: Tender Project (Detailed Design)
- 2012: Financing finally approved by Stortinget
- 2012: Tender documents finalised
- 2012 (Oct): Road and rock works tendered
- 2013 (Feb): Concrete works tendered – contract in June
- 2013 (Apr): Steel and cable works tendered – contract in August
- 2017: Bridge to be completed

## Bridge layout


### Challenges:

- Aerodynamic issues
- Inclined cable system
- Pylon foundations at level -30 m
- Transition from Clients standard rules to Eurocode during the project period
- Eurocode – Hålogaland Bridge is the first suspension bridge in Norway designed in accordance with Eurocode
- International contractors and suppliers?
  - Text on all drawings is in Norwegian as well as English
  - Particular specifications prepared in Norwegian as well as English

## Bridge layout

### Characteristics:


- Single span suspension bridge
- Second longest main span in Norway, 1145 m
- Span to sag ratio is 9.5
- Cables anchored directly to the rock
- Vertical navigation clearance 40 m above high water



## Bridge deck

### Cross section:

- Closed steel box girder
- Total width of bridge deck 18.6 m






## Bridge deck


### General arrangement:

- Deck panel: 14 mm deck plate, 6 mm trough stiffeners
- Bottom panel: 8 mm bottom plate, 6 mm trough stiffeners
- Diaphragms each 4.0 m
- Steel grade: NS EN 10025 S355N or M
- Steel quantity 7100 t – equivalent to 480 kg/m<sup>2</sup>






## Bridge deck




COWI

# Bridge deck



COWI

## Bridge deck





COWI



## Main cables

### General arrangement:

- 5.38 mm wires – breaking strength 1770 MPa
- Design is based on air spinning as construction method – similar to Hardanger Bridge
- 19 strands in main span – each having 328 wires
- 6232 wires in total - area 0.142 m<sup>2</sup>
- Cable diameter after compaction 0.478 m
- Additional strands in side spans due to local site constraints
- Tender is also open for PPWS as construction method – 60 strands in main span each having 91 wires of 5.75 mm diameter
- Steel quantity approx 4000 t



## Main cables

### Distribution of unfactored tension for 1770 MPa cables

---

Dead load, cables	16%
Dead load, steel deck	40%
Dead load, pavement	18%
Dead load, equipment	4%

---

<b>Dead load, total</b>	<b>78%</b>
Traffic	16%
Wind and temperature	6%

---

# Main cables

## Application of high strength steel

### Cable wires – breaking strength:

- 1570 MPa – Storebælt, Denmark (opened 1998)
- 1770 MPa – Akashi-Kaikyo, Japan (opened 1998)
- 1860 MPa – Yi Sun-Sin, Korea (opened 2012)
- 1960 MPa – 3 bridges under construction, Korea (planned 2014-2018)

General data for main cables	Unit	1570 MPa	1770 MPa	1860 MPa
Cable area	m <sup>2</sup>	0.165	<b>0.142</b>	0.133
Cable, diameter	mm	515	<b>478</b>	464
Cable steel quantity	t	4675	<b>4020</b>	3780



## Main cables Application of high strength steel

Cable wire strength	Area	$\Delta$ -quantity	Deflection	Cable diameter
1570 MPa	116%	+ 655 t	89%	0.52 m
<b>1770 MPa</b>	<b>100%</b>	-	<b>100%</b>	<b>0.48 m</b>
1860 MPa	94%	- 240 t	105%	0.46 m


### Conclusions:

- Cable forces due to dead load and cable quantities are reduced by adopting the highest possible cable wire strength
- Thereby significant cost savings are obtained in cables and anchorages
- Related savings are obtained in pylons, foundations and construction time
- Smaller wind load due to smaller cable diameter
- Slightly increased deflections

# Pylons

## General arrangement:




- Slender
- A-shaped, concrete, inclined cable planes
- Simple geometrical shape
- Light appearance due to tapering downwards
- Landmark for the region



## Cable structures Saddles

### Tower saddles:

- Welded steel structures
- Steel grade:  
NS EN 10025 S460N eller M
- Ribs: 50-60 mm
- Troughs: 80-120 mm
- Quantity approx 50 t
- "Open" structures – easy to inspect and maintain






# Cable structures

## Hangers

### General arrangement:

- Locked coil cables – 130 t
- EN 12385-10 – 1570 MPa
- Min breaking load 4.89 MN
- Diameter 70 mm
- Painted








# Cable structures

## Cable clamps

### General arrangement:

- Cast steel or welded steel structures – 50 t
- Membrane: 20 mm
- Eye plate: 55 mm, 15 mm cheek plates
- Stål grade: Cast steel NS EN 10293 G20MN5+QT eller NS EN 10025 S355NL
- Bolts easy to inspect and replace



## Aerodynamic issues

### Challenges:


- Document sufficient critical wind speed
- Avoid vortex shedding excitation of the steel box girder




# Critical wind speed Background

Requirement for Hålogaland bridge is 63.1 m/s


Documented critical wind speed for box girder suspension bridges



# Critical wind speed Wind tunnel tests




Critical  
wind speed:  
71 m/s



## Vortex shedding excitation

The box section is arranged in such a way that the slope of the lower inclined side plates is at 15.8 degrees in relation to the horizontal bottom plate




Thereby the sensitivity to vortex shedding excitation is reduced and it is not required to install guide vanes

# Corrosion Protection Systems for Cables

## New system:

- Dehumidification by dry air flow through the cables in addition to galvanizing of the cable wires
- Effectiveness is proven on suspension bridges in Denmark, Sweden, France and Japan



## Background for new system:

- Nowadays design lifetime up to 200 years is required (Messina Bridge)
- Life Cycle Costs for bridges shall be minimised
- System is developed based on experience gained from application of dehumidification systems in closed steel box girders



# Corrosion Protection Systems for Cables

## Features of dehumidification system:

- Complete corrosion protection of the cables
- Cables enclosed in an atmosphere with relative humidity below 60% - thereby corrosion cannot occur
- System provides overpressure in the cables - thereby water/moisture cannot enter the cables through any leaks


## Dehumidification system comprises 3 major components:

- Sealing system for the cables
- Dehumidification system producing and blowing dry air through the cables
- Control and monitoring system for system functionality, relative humidity, temperature, flow and pressure

# Corrosion Protection Systems for Cables

## Component 1: sealing system:

- Elastomeric wrap for cable sections between cable bands
- Applied under tension with a 50% overlap
- Special details developed for cable bands etc. using combinations of sealer strips and adhesive caulk



# Corrosion Protection Systems for Cables

## Component 2: dehumidification system:



- Produces dry air and blows it through the cables – max 40% relative humidity at injection points
- Overpressure inside the sealed cables - at injection points max. 2.5 kPa
- Components: dehumidification plants, injection points and exhaust points



# Corrosion Protection Systems for Cables

## Component 3: control and monitoring system:

- Temperature, relative humidity, flow and pressure are measured at all injection and exhaust sleeves for permanent monitoring of system operation and documentation of corrosion protection





# Corrosion Protection Systems for Cables

## Hålogaland Bridge:

- Handbook 185 requires dehumidification of main cables

